

UL1007	PVC 电线 Pvc wire <hr/> 设备内配线用电线 Appliance wiring material
--------	---

产品说明 Product description

- | | |
|--|--|
| <ul style="list-style-type: none"> ● 额定 80°C, 300V ● 标准 UL Subject 758 ● 特性 <ul style="list-style-type: none"> 1. 难燃性 UL: VW-1, CSA: FT1 ● 用途 <ul style="list-style-type: none"> 1. 电气, 电子设备的内部配线及
 仪表配线 ● 构造 | <ul style="list-style-type: none"> ◆ Rating 80°C, 300V ◆ Standard UL Subject 758 ◆ Features <ul style="list-style-type: none"> 1. Flammability VW-1, FT1 ◆ Application <ul style="list-style-type: none"> 1. Internal wiring of electrical and electronic
 equipment ◆ Construction |
|--|--|



印字/Marking: EVERTOP (S) E117873 兄 AWM STYLE 1007 (16~30)AWG VW-1 80°C 300V
 CSA LL82009 TYPE TR-64 (16~30) AWG 90°C FT1 LM

Part No	导体 Conductor		绝缘体 Insulation		外径 Dia	最大导体电阻
	AWG Size	构成 Stranding No. /mm	绝缘厚度 Insulation Thickness	材料 Material	Overall Diameter (mm)	Max. cond. resistance at 20°C (Ω /km)
E100730	30	7/0.10	0.38	PVC	1.1	381
E100728	28	7/0.127	0.38	PVC	1.2	239
E100726	26	7/0.16	0.38	PVC	1.3	150
E100724	24	11/0.16	0.38	PVC	1.4	94.2
E100722	22	17/0.16	0.38	PVC	1.6	59.4
E100720	20	21/0.178	0.38	PVC	1.8	36.7
E100718	18	34/0.178	0.38	PVC	2.1	23.2
E100716	16	26/0.254	0.38	PVC	2.4	14.6