

UL1430	XL-PVC 电线 XL-PVC wire
	设备内配线用电线 Appliance wiring material

产品说明 Product description

- | | |
|---|--|
| <ul style="list-style-type: none"> ● 额定 105°C, 300V ● 标准 UL Subject 758 ● 特性 <ul style="list-style-type: none"> 1. 难燃性 UL: VW-1, CSA: FT1 ● 用途 <ul style="list-style-type: none"> 1. 电气, 电子器具内部配线及仪表配线 ● 构造 | <ul style="list-style-type: none"> ◆ Rating 105°C, 300V ◆ Standard UL Subject 758 ◆ Features <ul style="list-style-type: none"> 1. Flammability VW-1, FT1 ◆ Application <ul style="list-style-type: none"> 1. Internal wiring of electrical and electronic equipment. ◆ Construction |
|---|--|



印字/Marking: EVERTOP (S) E117873 兄 AWM STYLE 1430 (18~28)AWG VW-1 105°C 300V CSA LL82009 AWM IA 105°C 300V FT1 (XL-PVC) LM

Part No	导体 Conductor		绝缘体 Insulation		外径 Dia	最大导体电阻
	AWG Size	构成 Stranding No. /mm	绝缘厚度 Insulation Thickness	材料 Material	Overall Diameter (mm)	Max. cond. resistance at 20°C (Ω/km)
E143028	28	7/0.127	0.38	XL-PVC	1.20	239
E143026	26	7/0.16	0.38	XL-PVC	1.30	150
E143024	24	11/0.16	0.38	XL-PVC	1.40	94.2
E143022	22	17/0.16	0.38	XL-PVC	1.60	59.4
E143020	20	21/0.178	0.38	XL-PVC	1.80	36.7
E143018	18	34/0.178	0.38	XL-PVC	2.05	23.2