

UL1571	PVC 电线 Pvc wire
	设备内配线用电线 Appliance wiring material

■ 产品说明 Product description

- | | |
|--|--|
| <ul style="list-style-type: none"> ● 额定 80°C, 300V ● 标准 UL Subject 758 ● 特性 <ul style="list-style-type: none"> 1. 难燃性 UL: VW-1, CSA: FT1 ● 用途 <ul style="list-style-type: none"> 1. 电气回路内部配线及仪表配线 ● 构造 | <ul style="list-style-type: none"> ◆ Rating 80°C, 300V ◆ Standard UL Subject 758 ◆ Features <ul style="list-style-type: none"> 1. Flammability VW-1, FT1 ◆ Application <ul style="list-style-type: none"> 1. Internal wiring of electrical and electronic equipment ◆ Construction |
|--|--|



印字/Marking: EVERTOP (S) E117873 兄 AWM STYLE 1571 (22~28)AWG VW-1 80°C 30V CSA LL82009 AWM IA 80°C 30V FT1 LM

Part No	导体 Conductor		绝缘体 Insulation		外径 Dia	最大导体电阻
	AWG Size	构成 Stranding No. /mm	绝缘厚度 Insulation Thickness	材料 Material	Overall Diameter (mm)	Max. cond. resistance at 20°C (Ω /km)
E157132	32	7/0.08	0.18	SR-PVC	0.60	543
E157130	30	7/0.10	0.18	SR-PVC	0.88	381
E157128	28	7/0.127	0.18	SR-PVC	0.95	239
E157126	26	7/0.16	0.18	SR-PVC	1.05	150
E157124	24	11/0.16	0.18	SR-PVC	1.20	94.2
E157122	22	17/0.16	0.18	SR-PVC	1.30	59.4